



### Specs

|                              |   |
|------------------------------|---|
| Projector type               | 3 LCD system  |
| Resolution                   | WUXGA - 1920 x 1200   |
| Brightness                   | 5200 Lumens   |
| Aspect ratio                 | 16:10   |
| Lamps                        | High-pressure mercury lamp 330 W type<br>High-pressure mercury lamp 275 W type  |
| Lamp lifetime                | 2500H(High)<br>3500H(Standard)  |
| Inputs                       | 1x 5BNC (RGB / Y Pb Pr)<br>1x Audio : Stereo mini jack<br>1x Mini D-sub 15-pin (RGB)<br>1x Audio : Stereo mini jack<br>1x DVI-D (HDCP support)<br>1x HDMI (Digital RGB/Y Pb Pr, Digital Audio)<br>1x S VIDEO IN Mini DIN-4pin<br>2x Audio : Pin jack x2 (shared with VIDEO IN)<br>1x Pin Jack<br>1x Monitor OUT Mini D-sub 15-pin<br>1x Audio OUT Stereo mini jack (variable out) |
| Control / Network connection | RS-232C connector: D-sub 9-pin (female)<br>LAN connector: RJ-45, 10BASE-T/100BASE-TX<br>Control S input connector: Stereo mini jack,<br>Plug in power DC 5 V  |
| Power requirements           | AC 100V to 240V, 4.6A to 1.9A, 50Hz/60Hz  |
| Max power                    | 460 W   |
| Dimensions (Wx-LxH)          | 15" x 18" x 6"  |
| Weight                       | 18 lb 5 oz  |